







NOTES/SPECIFICATIONS:

5.

- 1. 2. 3. 4. CLEAR APERTURE: > Ø 22.9mm

CLEAR APERIURE: > Ø 22.9mm

PARALLELISM: <3 arcmin

SURFACE QUALITY (\$1): 40-20 SCRATCH-DIG

SURFACE FLATNESS (\$1): \(\lambda\).710 AT 633nm

(\$2): FINE GRIND

COATING: PROTECTED SILVER

Ravg: >97% FROM 450nm - 2\(\lambda\)m

Ravg: >95% FROM 2\(\lambda\)m - 20\(\lambda\)m

AOI: 0° TO 45°

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

| | DRAWING PROJECTION | | | THORLABS www.thorlabs.com | | |
|--|--|------|-----------|---------------------------------------|-------------------|-----|
| | | NAME | DATE | ϕ 25.4mm PROTECTED SILVER MIRROR | | |
| | DRAWN | BAG | 26/OCT/10 | | | |
| | APPROVAL | DS | 18/NOV/22 | MATERIAL FLICED CILICA | | REV |
| | COPYRIGHT © 2022 BY THORLABS | | | FUSED SILIC | A | D |
| | VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS | | | PF10-03-P01 | APPROX WEIGHT 7 g | |