





NOTES/SPECIFICATIONS:

- 1. 2. 3. 4.

- 5.

CLEAR APERTURE: > Ø91.4mm
PARALLELISM: <3arcmin
SURFACE QUALITY (S1): 40-20 SCRATCH-DIG
SURFACE FLATNESS (S1): \(\lambda\)/10 AT 633nm
(S2): FINE GRIND
COATING: PROTECTED SILVER
Ravg: >97% FROM 450nm - 2\(\rambda\)m
Ravg: >95% FROM 2\(\rambda\)m - 20\(\rambda\)m
AOI: 0° TO 45°

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS.com		
	NAME	DATE			D O D
DRAWN	BAG	26/OCT/10	ϕ 101.6mm PROTECTED SILVER MIRRO		ROR
APPROVAL	DS	18/NOV/22			REV
COPYRIGHT © 2022 BY THORLABS			FUSED SILICA		D
VALUES IN DADENITUESIS ADE CALCULATED			ITEM #	APPROX WE	IGHT

PF40-03-P01

340 g

VALUES IN PARENTHESIS ARE CALCULATED

AND MAY CONTAIN ROUNDOFF ERRORS